



ACRYLICFOAM® VP MP & EP & LP

Density	VP	MP-FC	MP-MC	EP	LP
(kg/m³)	Fine Cell	Fine Cell	Medium Cell	Medium Cell	Medium Cell
31		31MP-FC	31MP-MC	31EP	
51		51MP-FC	51MP-MC	51EP	51LP
71		71MP-FC	71MP-MC	71EP	71LP
110		110MP-FC	110MP-MC	110EP	110LP
Heat deflection temperature	163°C	165°C	165°C	155°C	165°C
Compatible with resin system	Low viscosity resin	Low viscosity resin	Medium viscosity resin	Medium viscosity resin	Medium viscosity resin
Curing conditions	medium temperature curing resin system	medium temperature curing resin system	medium temperature curing resin system	low-medium temperature curing resin system	low-medium temperature curing resin system
Applicable usage	Fish drift, medical, wind power, automobile	Fish drift, medical, wind power, automobile	Fish drift, medical, wind power, automobile	Medical, wind power, automotive	Medical, wind power, automotive

Density (kg/m³)	Maximum board size	Thickness tolerance
31	2500*1250*100mm	±0.5mm
51	2500*1250*90mm	±0.5mm
71	2500*1250*80mm	±0.5mm
110	2160*1100*70mm	±0.5mm
200	1850*900*60mm	±0.5mm

Arch Industrial (HK) Limited

Mobile: +86 139-1621-2034

Email: pei.hu@archcell.net

Address: Rooms 05-15, 13A/F., South Tower, World Finance Centre, Harbour City, 17 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong.

